



YANMAR



MINI EXCAVATOR

SV10

Compact, versatile and intuitive, the new SV10 is purpose-built for indoor work, landscaping and all activities requiring a truly ultra-narrow machine.

Able to pass through standard EU doorways and operate confidently in tight spaces, it combines variable track width with a wide working range for impressive flexibility. Improved ergonomics with side levers ensure intuitive operation, while Yanmar-trusted reliability and a tilting engine bonnet make daily maintenance quick and effortless.

- ULTRA-NARROW DESIGN
- VARIABLE UNDERCARRIAGE
- WIDE WORKING RANGE
- SIDE-LEVER ERGONOMICS
- EXTENDED REACH CAPABILITY
- ROPS PROTECTION
- EASY MAINTENANCE





TECHNICAL SPECIFICATIONS

[WEIGHT +/-2% (EN STANDARDS)]

| | Weight | Ground pressure |
|--|----------|--------------------------|
| Operating weight (rubber tracks – with operator, quick hitch & bucket) | 1 180 kg | 0,28 kgf/cm ² |
| Transport weight (rubber tracks – without quick hitch & bucket) | 1 055 kg | 0,31 kgf/cm ² |

[ENGINE & HYDRAULIC SYSTEM]

| | |
|--|------------------------------------|
| Type | 3TNV70-WBVB1 |
| Net Power | 9,2 kW – 2000 rpm |
| Gross Power | 9,3 kW – 2000 rpm |
| Displacement | 0,854 liter |
| Maximum torque | 47,6 – 51,8 N.m (1500 +/- 100 rpm) |
| Maximum pressure | 190 bar |
| 1 double variable displacement piston pump | 2 x 11,14 l/min |
| 1 gear pump | 6.79 l/min |

[PERFORMANCE]

| | |
|---------------------------------|-------------------------|
| Travel speed [Low / High] | 1,8 / 3,6 km/h |
| Digging force [Arm] | 5.2 kN |
| Digging force [European Bucket] | 7,6 kN |
| Noise level | LwA: XX dBA/LpA: XX dBA |

DIMENSIONS

| | | | |
|---------------------------------------|------------------|--|-----------|
| Overall length | 2 810 mm | Max. digging depth – Blade lowered | 1 955 mm |
| Overall length with blade at the back | 2 985 mm | Max. digging reach | 3 180 mm |
| Overall height | 2 300 mm | Max. dumping height | 2 010 mm |
| Overall width | 740 mm / 990 mm* | Boom swinging (base to left/right) | 60° / 60° |
| Length of track on ground | 970 mm | Arm length | 905 mm |
| Blade distance | 840 mm | Rear turning radius with counterweight | 590 mm |
| Minimum ground clearance | 125 mm | Front turning radius with boom swing | 935 mm |

* Retracted / Extended undercarriage

Yanmar Compact Equipment EMEA

GB_SPEC_SV10_1225



www.yanmar.com

**BUILDING
WITH YOU**